

## Emergency Light 2x3W



### Application

Designed for lighting commercial and contract spaces. The Lighting solutions designed for global markets, compatible with mains voltages: 220-240V.  
CE ISO, NTP IEC 60598-2-22 y NFP A-101



### Product Specification

|                               |                         |
|-------------------------------|-------------------------|
| <b>Model:</b>                 | KYR-EM04895             |
| <b>Power:</b>                 | 2X3W (LED Type SMD2835) |
| <b>Working time:</b>          | 1.5 hours - Automatic   |
| <b>Charge time:</b>           | 20 hours                |
| <b>Battery: type</b>          | Lead-Acid               |
| <b>Luminous lux:</b>          | 365lm / por faro        |
| <b>CCT:</b>                   | 6500K                   |
| <b>CRI:</b>                   | 80                      |
| <b>ON-OFF Switch</b>          | 2                       |
| <b>Input voltaje:</b>         | AC 110 / 220V ( ± 10%)  |
| <b>IP rating:</b>             | 65                      |
| <b>Dimension (mm):</b>        | L270xW80xH295           |
| <b>Full charge indicator:</b> | Green                   |
| <b>Life time:</b>             | 50 000 hours            |
| <b>Working temp.:</b>         | -20°~ +40°              |
| <b>Housing material:</b>      | Metal                   |
| <b>Diffuser:</b>              | Optical transparent     |
| <b>Finishing:</b>             | White                   |
| <b>IK:</b>                    | 07                      |